



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H10B-SFH-1L-CV-2M25	19300100296	M25
2	H10B-SFH-1L-CV-2M32	19300100297	M32
3	H10B-SFH-1L-CV-2PG21	09300100297	PG21
4	H10B-SFH-1L-CV-2PG29	09300100298	PG29

技术参数:
 - 材料: 压铸铝
 - 盖子材料: PC
 - 表面处理: 粉末喷涂
 - 颜色: Grey (灰色)
 - 温度范围: -40℃ - +125℃
 - 防护等级: IP65 (联锁状态, IEC 60529)
 - 联锁元件:
 锁扣方式: 单扣
 材料: 金属 (铁) 镀锌
 - 出线方向: 侧出线
 - 出线孔数: 2
 - 螺纹规格: M/PG
 - 密封元件: NBR

Technical specification:
 - Material: Aluminium die-cast
 - Material, cover: PC
 - Surface: powder-coated
 - Colour: (grey)
 - Temperature range:
 -40℃ - +125℃
 - Degree of Protection: IP65
 (acc.to IEC 60529 for coupled connector)
 - Locking element:
 locking type: single locking latch
 material: metal galvanized/nickel plating
 - Cable entry: side entry
 - No. of cable entries: 2
 - Thread size: M/PG
 - Hoods/Housings sealing: NBR

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/			
产品代号 Part Code:		H10B-SFH-1L-CV-2M/2PG		产品料号 PART NO:			
Date:	2018.08.18	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/	Tang	1/1