



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H16B-SEH-2L-M25	19300160536	M25
2	H16B-SEH-2L-M32	19300160537	M32
3	H16B-SEH-2L-M40	19300160538	M40
4	H16B-SEH-2L-PG21	09300160530	PG21
5	H16B-SEH-2L-PG29	09300160531	PG29

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
锁扣方式: 金属双扣
材料: 不锈钢
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M/PG

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
-40℃ - +125℃
- Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
locking type: double locking latch
material: stainless steel
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M/PG

ZJHK 浙江昊科电气有限公司 ZHEJIANG HAOKO ELECTRICAL CO.,LTD		图号 Drawing No:	/
产品代号 Part Code:		产品料号 PART NO:	/
日期 Date:	2020.8.28	比例 Scale	1.5:1
		版本 REV	HK-1
		重量 Weight	/
		数量 Qty	/
		绘图 Drawn	Tang
		页 SHEET	1/1
All Dimensions in mm Original Size DIN A 4			