



| 序号 | 型号 (Type) | 料号 (PART NO) | 螺纹规格 Thread size |
|----|---------------------|--------------|---------------------|
| 1 | H16B-SFH-1L-CV-M32 | 19300160257 | M32 |
| 2 | H16B-SFH-1L-CV-PG21 | 09300160255 | PG21 |
| 3 | H16B-SFH-1L-CV-PG29 | 09300160256 | PG29 |

技术参数:

- 材料: 压铸铝
- 盖子材料: PC
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 金属 (铁) 镀锌
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:

- Material: Aluminium die-cast
- Material, cover: PC
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
 - 40℃ - +125℃
- Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - locking type: single locking latch
 - material: metal galvanized/nickel plating
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M/PG
- Hoods/Housings sealing: NBR

| | | | | | | | |
|---|---|---------------------|------|------------------|-----|--------|-------|
| 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD | | 图号 Drawing No: | | / | | | |
| 产品代号 Part Code: | | H16B-SFH-1L-CV-M/PG | | 产品料号 PART NO: | | | |
| Date: | 2018.08.16 | Scale | REV | Weight | Qty | Drawn: | SHEET |
| | All Dimensions in mm Original Size DIN A 4 | 1:2 | HK-1 | / | / | Tang | 1/1 |