



| 序号 | 型号 (Type) | 料号 (PART NO) | 螺纹规格 Thread size |
|----|-------------------|--------------|---------------------|
| 1 | H16B-SFH-2L-2M25 | 19300160271 | M25 |
| 2 | H16B-SFH-2L-2M32 | 19300160272 | M32 |
| 3 | H16B-SFH-2L-2M40 | 19300160273 | M40 |
| 4 | H16B-SFH-2L-2PG21 | 09300160270 | PG21 |
| 5 | H16B-SFH-2L-2PG29 | 09300160271 | PG29 |

技术参数:
 - 材料: 压铸铝
 - 表面处理: 粉末喷涂
 - 颜色: Grey (灰色)
 - 温度范围: -40°C - +125°C
 - 防护等级: IP65 (联锁状态, IEC 60529)
 - 联锁元件:

锁扣方式: 金属双扣
 材料: 不锈钢
 - 出线方向: 侧出线
 - 出线孔数: 2
 - 螺纹规格: M/PG
 - 密封元件: NBR

Technical specification:
 - Material: Aluminium die-cast
 - Surface: powder-coated
 - Colour: (grey)
 - Temperature range:
 -40°C - +125°C
 - Degree of Protection: IP65
 (acc.to IEC 60529 for coupled connector)
 - Locking element:
 locking type: double locking latch
 material: stainless steel
 - Cable entry: side entry
 - No. of cable entries: 2
 - Thread size: M/PG
 - Hoods/Housings sealing: NBR

| | | | | | | | |
|--|---|--------------------|------|------------------|-----|--------|-------|
| ZJKK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD | | 图号 Drawing No: | | / | | | |
| 产品代号 Part Code: | | H16B-SFH-2L-2M/2PG | | 产品料号 PART NO: | | / | |
| Date: | 2018.08.16 | Scale | REV | Weight | Qty | Drawn: | SHEET |
| | All Dimensions in mm Original Size DIN A 4 | 1:2 | HK-1 | / | / | Tang | 1/1 |