



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H24B-CCT-1L-M25	19300241751	M25
2	H24B-CCT-1L-M32	19300241752	M32
3	H24B-CCT-1L-PG21	09300241750	PG21
4	H24B-CCT-1L-PG29	09300241751	PG29

技术参数:
- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 锁扣方式: 单扣
 材料: 金属 (铁) 镀锌
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:
- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
 -40℃ - +125℃
- Degree of Protection: IP65
 (acc.to IEC 60529 for coupled connector)
- Locking element:
 locking type: single locking latch
 material: metal galvanized/nickel plating
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M/PG
- Hoods/Housings sealing: NBR

ZJKK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD		图号 Drawing No:		/	
产品代号 Part Code:		H24B-CCT-1L-M/PG		产品料号 PART NO:	
Date:	2018.08.10	Scale	REV	Weight	Qty
⊕	All Dimensions in mm Original Size DIN A 4	1:1.5	HK-1	/	/
Date:			2018.08.10	Scale	REV
Weight			Qty	Drawn:	SHEET
Tang					1/1