



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H24B-CCTH-2L-M32	19300240737	M32
2	H24B-CCTH-2L-M40	19300240738	M40
3	H24B-CCTH-2L-PG21	09300240730	PG21
4	H24B-CCTH-2L-PG29	09300240731	PG29

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40°C - +125°C
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:

锁扣方式: 金属双扣

材料: 不锈钢

- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range: -40°C - +125°C
- Degree of Protection: IP65 (acc.to IEC 60529 for coupled connector)
- Locking element: locking type: double locking latch material: stainless steel
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M/PG
- Hoods/Housings sealing: NBR

ZJKK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/	
产品代号 Part Code:		H24B-CCTH-2L-M/PG		产品料号 PART NO:	
Date:		2018.09.26	Scale	REV	Weight
All Dimensions in mm Original Size DIN A 4		1:2	HK-1	/	/
Qty		Drawn:	Tang		SHEET
					1/1