



| 序号 | 型号 (Type) | 料号 (PART NO) | 螺纹规格 Thread size |
|----|------------------|--------------|---------------------|
| 1 | H24B-SEH-2B-M25 | 19300240546 | M25 |
| 2 | H24B-SEH-2B-M32 | 19300240547 | M32 |
| 3 | H24B-SEH-2B-M40 | 19300240548 | M40 |
| 4 | H24B-SEH-2B-PG21 | 09300240540 | PG21 |
| 5 | H24B-SEH-2B-PG29 | 09300240541 | PG29 |

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40°C - +125°C
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M/PG

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range: -40°C - +125°C
- Degree of Protection: IP65 (acc.to IEC 60529 for coupled connector)
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M/PG

| | | | | | | | |
|--|---|-------------------|------|--------|-----|--------|-------|
| 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD | | 图号 Drawing No: | | / | | | |
| 产品代号 Part Code: H24B-SEH-2B-M/PG | | 产品料号 PART NO: | | / | | | |
| Date: | 2019.02.10 | Scale | REV | Weight | Qty | Drawn: | SHEET |
| | All Dimensions in mm Original Size DIN A 4 | 1:1.5 | HK-1 | / | / | Tang | 1/1 |