



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H24B-SEH-4B-M25	19300240526	M25
2	H24B-SEH-4B-M32	19300240527	M32
3	H24B-SEH-4B-M40	19300240528	M40
4	H24B-SEH-4B-PG21	09300240520	PG21
5	H24B-SEH-4B-PG29	09300240521	PG29

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40°C - +125°C
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M/PG

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range: -40°C - +125°C
- Degree of Protection: IP65 (acc.to IEC 60529 for coupled connector)
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M/PG

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/			
产品代号 Part Code: H24B-SEH-4B-M/PG		产品料号 PART NO:		/			
Date:	2019.02.10	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:1.5	HK-1	/	/	Tang	1/1