



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H24B-SFH-2L-M25	19300240231	M25
2	H24B-SFH-2L-M32	19300240232	M32
3	H24B-SFH-2L-M40	19300240233	M40
4	H24B-SFH-2L-PG21	09300240230	PG21
5	H24B-SFH-2L-PG29	09300240231	PG29

技术参数:
 - 材料: 压铸铝
 - 表面处理: 粉末喷涂
 - 颜色: Grey (灰色)
 - 温度范围: -40°C - +125°C
 - 防护等级: IP65 (联锁状态, IEC 60529)
 - 联锁元件:

锁扣方式: 金属双扣
 材料: 不锈钢

- 出线方向: 侧出线
 - 出线孔数: 1
 - 螺纹规格: M/PG
 - 密封元件: NBR

Technical specification:
 - Material: Aluminium die-cast
 - Surface: powder-coated
 - Colour: (grey)
 - Temperature range:
 -40°C - +125°C
 - Degree of Protection: IP65
 (acc.to IEC 60529 for coupled connector)
 - Locking element:
 locking type: double locking latch
 material: stainless steel
 - Cable entry: side entry
 - No. of cable entries: 1
 - Thread size: M/PG
 - Hoods/Housings sealing: NBR

ZJKK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/	
产品代号 Part Code:		H24B-SFH-2L-M/PG		产品料号 PART NO:	
Date:	2018.08.16	Scale	REV	Weight	Qty
☉	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/
Drawn:	Tang	SHEET		1/1	