



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H32A-TEH-2L-M25	19200320447	M25
2	H32A-TEH-2L-M32	19200320437	M32
3	H32A-TEH-2L-PG21	09200320430	PG21
4	H32A-TEH-2L-PG29	09200320431	PG29

- 技术参数:
- 材料: 压铸铝
 - 表面处理: 粉末喷涂
 - 颜色: Grey (灰色)
 - 温度范围: -40°C - +125°C
 - 防护等级: IP65 (联锁状态, IEC 60529)
 - 联锁元件:
 - 锁扣方式: 双扣
 - 材料: 金属 (铁) 镀锌
 - 出线方向: 顶出线
 - 出线孔数: 1
 - 螺纹规格: M/PG

- Technical specification:
- Material: Aluminium die-cast
 - Surface: powder-coated
 - Colour: (grey)
 - Temperature range:
 - 40°C - +125°C
 - Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
 - Locking element:
 - locking type: Double locking latch
 - material: metal galvanized/nickel plating
 - Cable entry: top entry
 - No. of cable entries: 1
 - Thread size: M/PG

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD		图号 Drawing No:		/			
产品代号 Part Code:		产品料号 PART NO:		/			
Date:	2018.08.16	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:1.5	HK-1	/	/	Tang	1/1