




序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H48B-SE-2B-M32	19300480547	M32
2	H48B-SE-2B-M40	19300480548	M40
3	H48B-SE-2B-M50	19300480549	M50
4	H48B-SE-2B-PG29	09300480540	PG29
5	H48B-SE-2B-PG36	09300480541	PG36
6	H48B-SE-2B-PG42	09300480542	PG42



技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: M/PG

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range: -40℃ - +125℃
- Degree of Protection: IP65 (acc.to IEC 60529 for coupled connector)
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: M/PG

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD		图号 Drawing No:		/			
产品代号 Part Code: H48B-SE-2B-M/PG		产品料号 PART NO:		/			
Date:	2018.08.16	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/	Tang	1/1