



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H6B-SFH-1L-MCV-M25	19300067256	M25
2	H6B-SFH-1L-MCV-M32	19300061257	M32
3	H6B-SFH-1L-MCV-PG21	09300062257	PG21
4	H6B-SFH-1L-MCV-PG29	09300062258	PG29

- 技术参数:
- 材料: 压铸铝
  - 盖子材料: 压铸铝
  - 表面处理: 粉末喷涂
  - 颜色: Grey (灰色)
  - 温度范围: -40°C - +125°C
  - 防护等级: IP65 (联锁状态, IEC 60529)
  - 联锁元件:
    - 锁扣方式: 单扣
    - 材料: 金属 (铁) 镀锌
  - 出线方向: 侧出线
  - 出线孔数: 1
  - 螺纹规格: M/PG
  - 密封元件: NBR

- Technical specification:
- Material: Aluminium die-cast
  - Material, cover: Aluminium die-cast
  - Surface: powder-coated
  - Colour: (grey)
  - Temperature range:
    - 40°C - +125°C
  - Degree of Protection: IP65  
(acc.to IEC 60529 for coupled connector)
  - Locking element:
    - locking type: single locking latch
    - material: metal galvanized/nickel plating
  - Cable entry: side entry
  - No. of cable entries: 1
  - Thread size: M/PG
  - Hoods/Housings sealing: NBR

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/				
产品代号 Part Code: H6B-SFH-1L-MCV-M/PG		产品料号 PART NO:		/				
Date:	2018.08.16	Scale	REV	Weight	Qty	Drawn:	SHEET	
	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/	Tang	1/1	